

FIREX

2.5 kg Fire Extinguisher with Metal Bracket

#FE25KG

www.firex.com.au

DESCRIPTION

2.5KG ABE fire extinguisher fitted with stainless steel vehicle bracket. One of FireX's most versatile fire extinguishers which can be fitted to a vehicle or wall. Other features include stainless steel handles, steel cylinder, brass valve and powder coated red finish.

Rating: 3A:40B:E.

Approved to AS/NZS 1841.5.

FEATURES

- Rugged epoxy coated steel cylinder with welded base for extra strength
- Resist corrosion, dents and punctures
- Special UV resistant paint
- EPDM type UV resistant discharge hoses
- 316 stainless steel handles and levers - suitable for marine use
- 316 stainless steel hose retaining clip and bands
- Supplied with vehicle mounting bracket
- Service maintenance tag fitted



APPLICATIONS

Fire Class	Example Application	Meets Requirement
Class A - Flammable Materials	• Paper, wood, textiles	• Yes
Class B - Flammable Liquids	• Flammable liquids, oil, paints, solvents	• Yes
Class E - Electrical Equipment	• Energised electrical fire, switch boards, electrical motors	• Yes

TECHNICAL SPECIFICATIONS

Capacity	• 2.5 kg	Overall Mass	• 4.2 kg
Fire Rating	• 3A:40B:E	Cylinder Material	• Steel, UV powder coat
Agent	• 90% MAP dry chemical powder	Handle Material	• Stainless steel
Operating Pressure	• 1000kPa - 15 sec discharge time	Valve Material	• Chrome plated brass
Dimensions	• 400mm H x 120mm dia	Hose Material	• EPDM, brass ferrules
Cylinder Thickness	• 1.20mm	Approvals	• AS/NZS 1841.5