





HD10 Series Plugs

Sold Individually

www.te.com

www.qvee.com.au






DESCRIPTION

These industry proven connectors are sealed to IP68 standards. Equipped with thermoplastic housing and silicon rubber seals, perfect for harsh environments. Takes size 16 pins. Rated at 13 Amps per circuit.

TECHNICAL SPECIFICATIONS

CONFIGURATIONS



3-16/3-96 3 size 16




5-16 5 size 16



6-96 6 size 16



9-16 9 size 16





Threading:

• X-16: Non threaded rear • X-96: Threaded rear

IP Rating

• IP68 rated

Operating Temperature

• -55 to 125°C



9-96 9 size 16

Voltage Rating

• 250 Volt DC

Flammability Rating

• UL 94V-1

PART NUMBERS

Part Number.	Dimensions (mm)	Terminals	Threaded	Descriptions
HD16-3-16S	• 27.14 W x 40.87 H x 27.14 L	• 3 x size 16	• No	• 3 circuit HD10 in-line plug. Takes pins
HD16-3-96S	• 27.1 W x 40.87 H x 27.15 L	• 3 x size 16	• Yes	• 3 circuit HD10 in-line plug with thread. Takes pins
HD16-5-16S	• 30.94 W x 40.87 H x 30.94 L	• 5 x size 16	• No	• 5 circuit HD10 in-line plug. Takes pins
HD16-6-96S	• 36.89 W x 40.61 H x 36.89 L	• 6 x size 16	• Yes	• 6 circuit HD10 in-line plug with thread. Takes pins
HD16-9-16S	• 40.35 W x 40.88 H x 40.35 L	• 9 x size 16	• No	• 9 circuit HD10 in-line plug. Takes pins
HD16-9-96S	• 41.46 W x 40.39 H x 41.46 L	• 9 x size 16	• Yes	• 9 circuit HD10 in-line plug with thread. Takes pins