



DELPHI

www.apativ.com

Packard Weatherpack Female Housings

Sold Individually

www.qvee.com.au



DESCRIPTION

Weatherpack connectors Triple ribbed silicone seals & are able to withstand chemicals, fluids and temperatures from -40°C to 125°C. Features a secure locking clip and locking indexing post to prevent mismatching. Rated 20A per circuit.

TECHNICAL SPECIFICATIONS


CONFIGURATIONS




QV12010996
1 x Pin




QV12010973
2 x Pins




QV12010717
3 x Pins



QV12010974
4 x Pins



QV12015024
4 x Pins



QV12010975
6 x Pins

Terminal Cable Size:

- QV12089040 - 3mm auto
- QV12124582 - 4mm auto
- QV12124587 - 5mm auto

Current Rating	• 20 Amps per circuit	Centreline Spacing	• 7.7mm
Cable Range	• 0.5-0.8mm ² (supplied terminals)	Materials	• Contacts: tin plated brass • Cable plug & Seal: Silicone • Housing: PA66
Operating Temperature	• -40°C to 125°C	Approvals	• ELV & RoHS approved
Resistance / Voltage Drop	• <10m @ 20mV / <3.0mV/Amp		

PART NUMBERS

Part Number.	Dimensions	Terminals	Descriptions
QV12010996	16mm x 17mm x 47mm	1 x Pin	1 circuit Packard Weatherpack female housing to take male pin
QV12010973	29mm x 17mm x 47mm	2 x Pins	2 circuit Packard Weatherpack female housing to take male pin
QV12010717	33mm x 17mm x 47mm	3 x Pins	3 circuit Packard Weatherpack female housing to take male pin
QV12010974	39mm x 17mm x 47mm	4 x Pins	4 circuit Packard Weatherpack female housing to take male pin
QV12015024	24mm x 25mm x 47mm	4 x Pins	Square 4 circuit Packard Weatherpack female housing to take male pin
QV12010975	55mm x 17mm x 47mm	6 x Pins	6 circuit Packard Weatherpack female housing to take male pin